

# OENOLOGICAL DISTILLATION UNIT

**Official method for the determination of the alcoholic strength by volume in wines, musts and spirits (according to EU Regulation 2676/90 and 2870/2000) and of the volatile acidity and sorbic acid.**

## Features:

- Steam distillation unit
- Steam generator automatically fed with demineralised water, having an electronic level control and automatic stop in the case of lack of water in the container
- Safety thermostat
- Automatic stop when reaching 200 ml of distillate
- Manual leveling of the distillate to 200 ml avoiding adding distilled water
- Automatic stop of refrigerating water at the end of distillation
- Optical display of minimal & maximal level of water in the steam generator and alarm
- Button to add distillate manually



**Automatic stop when reaching 200 mL**

## Technical Data:

Refrigeration water flow: 75 L/h.  
 Steam generator power: 1800 W  
 Water consumption (steam generator): 1,6 L/h  
 Distilled water reservoir: 10 L  
 Approx. distillation time: 7 min./200 mL  
 External dimensions (H x W x D): 855 x 385 x 350 mm

## Supplied with the following accessories:

- 1 distillation tube for 100 ml
- 1 distillation tube for 250 ml
- 1 volumetric flask of 200 ml.
- 1 reservoir of 10 liters for H<sub>2</sub>O.
- Connection tubing.

**H x L x D 855 x 385 x 350 mm**

**Power 1800 W**

**Weight 27 kg**